






DESCRIPTION规格			Brazilia – Indiana – Metallica – Osmoz – Poesy – Neopolis
Total thickness总厚度	EN ISO 24346 (EN 428)	mm	2
Wearlayer thickness耐磨层厚度	EN ISO 24340 (EN 429)	mm	> 1
Weight重量	EN ISO 23997 (EN 430)	g/sq.m	2580-2680
Width of sheet卷宽	EN ISO 24341 (EN 426)	cm	200
Length of sheet卷长	EN ISO 24341 (EN 426)	lm	20
CLASSIFICATION 类别			
Norm / Product specification产品规范	-	-	EN ISO 10582 (EN 649)
European classification产品分级	EN ISO 10874 (EN 685)	class	34 -43
Fire rating防火等级	EN 13 501-1	class	Bfl-s1
Static electrical propensity抗静电性	EN 1815	kV	< 2
Slip resistance (1) 防湿滑性	DIN 51 130	class	R10
PERFORMANCES性能			
Wear resistance耐磨性	EN 660.2	mm ³	≤ 2.0
Wear group耐磨等级	NF 189	group	T
Type binder content 粘合物分级	EN ISO 10582	type	I
Dimensional stability 尺寸稳定性	EN ISO 23999 (EN 434)	%	≤ 0.40
Residual indentation (requirement) 残余凹陷度 (要求值)	EN ISO 24343-1 (EN 433)	mm	≤ 0.10
Residual indentation (measure) 残余凹陷度(测 量值)	-	mm	≈ 0.02
Impact sound insulation隔音(隔声)性能	EN ISO 717-2	dB	8
Castor chair test (type W) 椅子脚轮测试	ISO 4918 (EN 425)	-	OK
Thermal conductivity热传导性	EN ISO 10456 (EN 12 524)	W/(m.K)	0.25
Colour fastness颜色稳定性	EN 20 105 - B02	degree	≥ 6
Surface treatment特殊维护处理	-	-	Evercare™
Chemical products resistance (2) 抗化学性	EN ISO 26987 (EN 423)	-	OK
Anti-bacterial activity (E. coli - S. aureus - MRSA) (3) 抑菌性能 (大肠杆菌和金黄色葡萄球菌)	ISO 22196	-	> 99 % inhibits growth
ENVIRONMENT / INDOOR AIR QUALITY			
TVOC after 28 days 28天后TVOC排放量	ISO 16000-6	µg/m ³	< 10
Certification 证书	-	-	FloorScore®
CE MARKING			
	EN 14041	   	

(1) For lifetime sustainable wet resistance, please refer to Tarasafe ranges.

对于永久抗湿滑产品，请关注Tarasafe系列产品

(2) Regarding the resistance to chemicals, please download the corresponding leaflet from our website.

关于抗化学性，请到网站下载相应产品单页。

(3) The implementation of an effective cleaning regime is the most important defence against infection.

实施有效的清洁方法是抗感染最重要的防御措施。